Shell	Gadus	S2 V	100	3

Version 3.4

Revision Date 13.10.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	: Shell Gadus S2 V100 3
Product code	: 001D8464

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture	:	Automotive and industrial grease.
Uses advised against	:	This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier	: Shell UK Oil Products Limited Shell Centre London SE1 7NA United Kingdom
Telephone Telefax	: (+44) 08007318888 :
Email Contact for Safety Data Sheet	: If you have any enquiries about the content of this SDS please email lubricantSDS@shell.com

1.4 Emergency telephone number

: +44-(0) 151-350-4595

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Chronic aquatic toxicity, Category 3 H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	No Hazard Symbol required	
Signal word	:	No signal word	
Hazard statements	:	PHYSICAL HAZARDS: Not classified as a physical hazard according to CLP criteria.	

Shell Gadus S2 V100 3

Version 3.4	Revision Date	13.10.2017	Print Date 14.10.2017
	H412	HEALTH HAZARDS: Not classified as a hea criteria. ENVIRONMENTAL H. Harmful to aquatic life effects.	
Precautionary statements	 Prevention: P273 Response: Storage: Disposal: P501 	Avoid release to the e No precautionary phra No precautionary phra Dispose of contents/ o approved waste dispo	ases. ases. container to an
Sensitising components	: Contains triazo May produce a	le derivatives. n allergic reaction.	

2.3 Other hazards

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used grease may contain harmful impurities.

High-pressure injection under the skin may cause serious damage including local necrosis. Not classified as flammable but will burn.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature	:	A lubricating grease containing highly-refined mineral oils and
		additives. The highly refined mineral oil contains <3% (w/w) DMSO-
		extract, according to IP346.

Hazardous components

Chemical name	CAS-No. EC-No. Registration	Classification (REGULATION (EC) No	Concentration [%]
	number	1272/2008)	
Alkylene-bis-	10254-57-6	Aquatic Chronic4;	1-3
(dialkyldithiocarbamat e)	233-593-1	H413	
Zinc naphthenate	84418-50-8 282-762-6	Aquatic Chronic3; H412	0.25 - 2.4

Shell Gadus S2 V100 3

Ve	rsion 3.4	Revisio	Print Date 14.10.2017		
	Zinc naphthenate	12001-85-3 234-409-2	Skin Irrit.2; H315 Aquatic Acute1; H400 Aquatic Chronic1; H410	0.25 - 2.4	
	Triazole derivative	91273-04-0 401-280-0	Skin Corr.1B; H314 Skin Sens.1A; H317 Aquatic Chronic1; H410	0.01 - 0.09	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Not expected to be a health hazard when used under normal conditions.
Protection of first-aiders	:	When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
If inhaled	:	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	:	Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
		When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop. Obtain medical attention even in the absence of apparent wounds.
In case of eye contact	:	Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
If swallowed	:	In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Most important symptoms an	d e	effects, both acute and delayed
Symptoms	:	Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas.

Ingestion may result in nausea, vomiting and/or diarrhoea.

4.2

SAFETY DATA SHEET Regulation 1907/2006/EC		
Shell Gadus S2 V100 3		
Version 3.4	Revision Date 13.10.2017	Print Date 14.10.2017
	Local necrosis is evidenced by delayed on tissue damage a few hours following inject	
4.3 Indication of any immediate me	edical attention and special treatment need	ded
Treatment	: Notes to doctor/physician: Treat symptomatically.	
	High pressure injection injuries require pro intervention and possibly steroid therapy, t damage and loss of function. Because entry wounds are small and do no seriousness of the underlying damage, sur determine the extent of involvement may b anaesthetics or hot soaks should be avoid can contribute to swelling, vasospasm and surgical decompression, debridement and foreign material should be performed unde anaesthetics, and wide exploration is esse	o minimise tissue ot reflect the rgical exploration to be necessary. Local ed because they l ischaemia. Prompt evacuation of er general

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media 5.2 Special hazards arising from	 Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. Do not use water in a jet. the substance or mixture
Specific hazards during firefighting	: Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
5.3 Advice for firefighters	
Special protective equipment for firefighters	: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Version 3.4

Revision Date 13.10.2017

Print Date 14.10.2017

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	: 6.1.1 For non emergency personnel:
	Avoid contact with skin and eyes.
	6.1.2 For emergency responders:
	Avoid contact with skin and eyes.

6.2 Environmental precautions

Environmental precautions	: Use appropriate containment to avoid environmental
	contamination. Prevent from spreading or entering drains,
	ditches or rivers by using sand, earth, or other appropriate
	barriers.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up	:	Shovel into a suitable clearly marked container for disposal or
		reclamation in accordance with local regulations.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.	Use the information in this data sheet as in assessment of local circumstances to help appropriate controls for safe handling, store	r aerosols. ion in this data sheet as input to a risk ocal circumstances to help determine
--	--	--

7.1 Precautions for safe handling

Advice on safe handling	: Avoid prolonged or repeated contact with skin.
	Avoid inhaling vapour and/or mists.
	When handling product in drums, safety footwear should be
	worn and proper handling equipment should be used.
	Properly dispose of any contaminated rags or cleaning
	materials in order to prevent fires.

7.2 Conditions for safe storage, including any incompatibilities

Other data	: Keep container tightly closed and in a cool, well-ventilated
	place. Use properly labeled and closable containers.

riogaian	011 1001/2	000, 20	
Shell	Gadus	S2 V1	003

Version 3.4	Revision Date 13.10.2017	Print Date 14.10.2017
	Store at ambient temperature.	
	Refer to section 15 for any additional spectrum covering the packaging and storage of the sector of	5
	The storage of this product may be subjue Pollution (Oil Storage) (England) Regula guidance may be obtained from the loca agency office.	itions. Further
Packaging material	: Suitable material: For containers or cont steel or high density polyethylene. Unsuitable material: PVC.	ainer linings, use mild
Container Advice	: Polyethylene containers should not be e temperatures because of possible risk o	
7.3 Specific end use(s)		
Specific use(s)	: Not applicable	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Oil mist, mineral		TWA	5 mg/m3	US. ACGIH Threshold Limit Values

Biological occupational exposure limits

No biological limit allocated. **Monitoring Methods**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Version 3.4

Revision Date 13.10.2017

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

8.2 Exposure controls

Engineering measuresThe level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Due to the product's semi-solid consistency, generation of mists and dusts is unlikely to occur.

Personal protective equipment

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection :	If material is handled such that it could be splashed into eyes, protective eyewear is recommended. Approved to EU Standard EN166.
Hand protection	
Remarks :	Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using

hell Gadus S2 V100 3		
ersion 3.4	Revision Date 13.10.2017	Print Date 14.10.2017
	gloves, hands should be washed and Application of a non-perfumed moist	
	For continuous contact we recommend breakthrough time of more than 240 for > 480 minutes where suitable glo short-term/splash protection we reco recognize that suitable gloves offerin may not be available and in this case time maybe acceptable so long as a and replacement regimes are followed a good predictor of glove resistance dependent on the exact composition Glove thickness should be typically g depending on the glove make and m	minutes with preference oves can be identified. For ommend the same, but ng this level of protection e a lower breakthrough ppropriate maintenance ed. Glove thickness is not to a chemical as it is of the glove material. greater than 0.35 mm
Skin and body protection	 Skin protection is not ordinarily required work clothes. It is good practice to wear chemical in the second practice to wear chemical in the	
Respiratory protection	: No respiratory protection is ordinarily conditions of use. In accordance with good industrial hy precautions should be taken to avoid If engineering controls do not mainta concentrations to a level which is ad health, select respiratory protection of specific conditions of use and meetin Check with respiratory protective equilation Where air-filtering respirators are su appropriate combination of mask and Select a filter suitable for combined p and vapours [Type A/Type P boiling meeting EN14387 and EN143.	ygiene practices, d breathing of material. ain airborne equate to protect worker equipment suitable for the ng relevant legislation. uipment suppliers. itable, select an d filter. particulate/organic gases
Thermal hazards	: Not applicable	
Hygiene measures	: Exposure to this product should be r reasonably practicable. Reference s Health and Safety Executive's public Essentials".	hould be made to the
Environmental exposure co	ntrols	
General advice	: Take appropriate measures to fulfill to relevant environmental protection leg contamination of the environment by Chapter 6. If necessary, prevent und being discharged to waste water. Wa	gislation. Avoid / following advice given in dissolved material from

Version 3.4	Revision Date 13.10.2017	Print Date 14.10.2017
	treated in a municipal or industrial w before discharge to surface water. Local guidelines on emission limits must be observed for the discharge vapour.	for volatile substances

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: Semi-solid at room temperature.
Colour	: light brown
Odour	: Slight hydrocarbon
Odour Threshold	: Data not available
рН	: Not applicable
Drop point	: 180 °CMethod: IP 396
Initial boiling point and boiling range	: Data not available
Flash point	: Remarks: Not applicable
Evaporation rate	: Data not available
Flammability (solid, gas)	: Data not available
Upper explosion limit	: Typical 10 %(V)
Lower explosion limit	: Typical 1 %(V)
Vapour pressure	: < 0.5 Pa (20 °C) estimated value(s)
Relative vapour density	: > 1estimated value(s)
Relative density	: 0.900 (15 °C)
Density	: 900 kg/m3 (15.0 °C) Method: Unspecified
Solubility(ies)	
Water solubility	: negligible
Solubility in other solvents	: Data not available
Partition coefficient: n-	: Pow: > 6(based on information on similar products)

Shell Gadus S2 V100 3

Version 3.4	Revision Date 13.10.2017	Print Date 14.10.2017
octanol/water		
Auto-ignition temperature	: > 320 °C	
Viscosity		
Viscosity, dynamic	: Data not available	
Viscosity, kinematic	: Not applicable	
Explosive properties	: Not classified	
Oxidizing properties	: Data not available	
9.2 Other information		
Conductivity	: This material is not expected to be a s	static accumulator.
Decomposition temperature	: Data not available	

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

Stable. No hazardous reaction is expected when handled and stored according to provisions

10.3 Possibility of hazardous reactions

Hazardous reactions	: Reacts with strong oxidising agents.
10.4 Conditions to avoid	
Conditions to avoid	: Extremes of temperature and direct sunlight.
10.5 Incompatible materials	
Materials to avoid	: Strong oxidising agents.
10.6 Hazardous decomposition p	roducts
Hazardous decomposition products	: Hazardous decomposition products are not expected to form during normal storage.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

SAFETY DATA SHEET

Regulation 1907/2006/EC Shell Gadue S2 V100 3

Shell Gadus S2 V100 3			
Version 3.4		Revision Date 13.10.2017	Print Date 14.10.2017
Basis for assessment	:	Information given is based on data o the toxicology of similar products.Un the data presented is representative whole, rather than for individual com	less indicated otherwise, of the product as a
Information on likely routes of exposure	:	Skin and eye contact are the primary although exposure may occur following	
Acute toxicity			
Product:			
Acute oral toxicity	:	LD50 rat: > 5,000 mg/kg Remarks: Expected to be of low toxic	city:
Acute inhalation toxicity	:	Remarks: Not considered to be an in normal conditions of use.	halation hazard under
Acute dermal toxicity	:	LD50 Rabbit: > 5,000 mg/kg Remarks: Expected to be of low toxic	city:

Skin corrosion/irritation

Product:

Remarks: Expected to be slightly irritating., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Serious eye damage/eye irritation

Product:

Remarks: Expected to be slightly irritating.

Respiratory or skin sensitisation

Product:

Remarks: For respiratory and skin sensitisation:, Not expected to be a sensitiser.

Components:

Triazole derivative:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Germ cell mutagenicity

Product:

: Remarks: Not considered a mutagenic hazard.

Carcinogenicity

Version 3.4

Revision Date 13.10.2017

Product:

Remarks: Not expected to be carcinogenic.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

Reproductive toxicity

Product:

Remarks: Not expected to impair fertility., Not expected to be a developmental toxicant.

STOT - single exposure

Product:

Remarks: Not expected to be a hazard.

STOT - repeated exposure

Product:

Remarks: Not expected to be a hazard.

Aspiration toxicity

Product:

Not considered an aspiration hazard.

Further information

Product:

Remarks: Used grease may contain harmful impurities that have accumulated during use. The concentration of such harmful impurities will depend on use and they may present risks to health and the environment on disposal., ALL used grease should be handled with caution and skin contact avoided as far as possible.

Remarks: High pressure injection of product into the skin may lead to local necrosis if the

Version 3.4

Revision Date 13.10.2017

product is not surgically removed.

Remarks: Slightly irritating to respiratory system.

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

Summary on evaluation of th Germ cell mutagenicity- Assessment		CMR properties This product does not meet the criteria for classification in categories 1A/1B.
Carcinogenicity - Assessment	:	This product does not meet the criteria for classification in categories 1A/1B.
Reproductive toxicity - Assessment	:	This product does not meet the criteria for classification in categories 1A/1B.

SECTION 12: Ecological information

12.1 Toxicity

:	Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).
:	Remarks: Expected to be harmful: LL/EL/IL50 10-100 mg/l
:	Remarks: Expected to be harmful: LL/EL/IL50 10-100 mg/l
:	Remarks: Expected to be harmful: LL/EL/IL50 10-100 mg/l
:	Remarks: Data not available
:	Remarks: Data not available
:	Remarks: Data not available
	: :

Version 3.4

Revision Date 13.10.2017

<u>Components:</u> Zinc naphthenate :	
M-Factor (Acute aquatic toxicity) Zinc naphthenate :	: 1
M-Factor (Acute aquatic toxicity) Triazole derivative :	: 1
M-Factor (Acute aquatic toxicity)	: 1
12.2 Persistence and degradabili	ity
Product:	
Biodegradability	: Remarks: Expected to be not readily biodegradable., Major constituents are expected to be inherently biodegradable, but contains components that may persist in the environment.
12.3 Bioaccumulative potential	
Product:	
Bioaccumulation	: Remarks: Contains components with the potential to bioaccumulate.
Partition coefficient: n- octanol/water	: Pow: > 6Remarks: (based on information on similar products)
12.4 Mobility in soil	
Product:	
Mobility	 Remarks: Semi-solid under most environmental conditions., If it enters soil, it will adsorb to soil particles and will not be mobile. Remarks: Floats on water.
12.5 Results of PBT and vPvB as	ssessment
Product:	
Assessment	: This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.
12.6 Other adverse effects	
Product:	
Additional ecological information	 Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities., Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential. Poorly soluble mixture., May cause physical fouling of aquatic organisms.

Version 3.4

Revision Date 13.10.2017

Print Date 14.10.2017

Mineral oil is not expected to cause any chronic effects to aquatic organisms at concentrations less than 1 mg/l.

SECTION 13: Disposal considerations

13.1 Waste treatment methods	
Product	 Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses
	Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.
Contaminated packaging	: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local legislation	
Waste catalogue	:
	EU Waste Disposal Code (EWC):
Waste Code	:
	12 01 12*
Remarks	: Disposal should be in accordance with applicable regional, national, and local laws and regulations.
	Classification of waste is always the responsibility of the end user.
	Hazardous Waste (England and Wales) Regulations 2005.

Version 3.4

Revision Date 13.10.2017

SECTION 14: Transport information

14.1 UN number		
ADR	: Not regulated as a dangerous good	
RID	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
ΙΑΤΑ	: Not regulated as a dangerous good	
14.2 Proper shipping name		
ADR	: Not regulated as a dangerous good	
RID	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
ΙΑΤΑ	: Not regulated as a dangerous good	
14.3 Transport hazard class		
ADR	: Not regulated as a dangerous good	
RID	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
ΙΑΤΑ	: Not regulated as a dangerous good	
14.4 Packing group		
ADR	: Not regulated as a dangerous good	
RID	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
ΙΑΤΑ	: Not regulated as a dangerous good	
14.5 Environmental hazards		
ADR	: Not regulated as a dangerous good	
RID	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
14.6 Special precautions for user		
Remarks	: Special Precautions: Refer to Chapter 7, Handling & Storage for special precautions which a user needs to be aware of or needs to comply with in connection with transport.) ,

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV)

: Product is not subject to Authorisation under REACH.

Volatile organic compounds : 0 %

Shell Gadus S2 V100 3	3	
Version 3.4	Revision Date 13.10.2017	Print Date 14.10.2017
Other regulations	: Environmental Protection Act 1990 (Safety at Work etc. Act 1974. Consul Pollution Prevention and Control Act 1995. Factories Act 1961. The Carria and Use of Transportable Pressure I Regulations 2011. Chemicals (Haza Packaging for Supply) Regulations 2 Substances Hazardous to Health Re amended). Merchant Shipping (Dang Pollutants) Regulations 1997. Repor and Dangerous Occurrences Regula Personal Protective Equipment Regu Protective Equipment at Work Regul Waste (England and Wales) Regulations 2 Control of Major Accident Hazards R amended). Renewable Transport Fu (as amended). Energy Act 2011. Em (England and Wales) Regulations 20 (England and Wales) Regulations 20 (England and Wales) Regulations 20 Planning (Hazardous Substances) A regulations. The Environmental Prote	imers Protection Act 1987. t 1999. Environment Act age of Dangerous Goods Equipment (Amendment) rd Information and 2009. Control of egulations 2002 (as gerous Goods and Marine ting of Injuries, Diseases ations 1995 (as amended). ulations 2002. Personal lations 1992. Hazardous tions 2005(as amended). Regulations 1999 (as tel Obligations Order 2007 vironmental Permitting 010 (as amended). Waste 011 (as amended). tet 1990 and associated ection (Controls on

The components of this product are reported in the following inventories:

EINECS	:	All components listed or polymer exempt.
TSCA	:	All components listed.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other information

REGULATION (EC) No 1272/2008	Classification procedure:
Chronic aquatic toxicity, Category 3,	Expert judgement and weight of evidence
H412	determination.

Full text of H-Statements

H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Aquatic Acute Acute aquatic toxicity

/ersion 3.4	Revision Date 13.10.2017	Print Date 14.10.201
Aquatic Chronic	Chronic aquatic toxicity	
Skin Corr.	Skin corrosion	
Skin Irrit.	Skin irritation	
Skin Sens.	Skin sensitisation	
Abbreviations and Acro		
	document can be looked up in re	
	scientific dictionaries) and/or we	bsites.
	ACGIH = American Conference	of Governmental Industrial
	Hygienists	
	ADR = European Agreement co	
	Carriage of Dangerous Goods b	y Road
	AICS = Australian Inventory of C	Chemical Substances
	ASTM = American Society for Te	esting and Materials
	BEL = Biological exposure limits	6
	BTEX = Benzene, Toluene, Eth	
	CAS = Chemical Abstracts Serv	
	CEFIC = European Chemical Inc	
	CLP = Classification Packaging	and Labelling
	COC = Cleveland Open-Cup	
	DIN = Deutsches Institut fur Nor	0
	DMEL = Derived Minimal Effect	
	DNEL = Derived No Effect Level	
	DSL = Canada Domestic Substa	ance List
	EC = European Commission	
	EC50 = Effective Concentration	
	ECETOC = European Center on	h Ecotoxicology and
	Toxicology Of Chemicals	
	ECHA = European Chemicals A	
	EINECS = The European Invent	tory of Existing Commercial
	Chemical Substances	
	EL50 = Effective Loading fifty	New Chemical Cubeteness
	ENCS = Japanese Existing and	New Chemical Substances
	Inventory	
	EWC = European Waste Code	atom of Classification and
	GHS = Globally Harmonised Sys	stem of Classification and
	Labelling of Chemicals	Passarch on Cancor
	IARC = International Agency for IATA = International Air Transpo	
	IC50 = Inhibitory Concentration	
	IL50 = Inhibitory Level fifty	inty
	IMDG = International Maritime D	Jangerous Goods
	INV = Chinese Chemicals Inven	
	IP346 = Institute of Petroleum	
	determination of polycyclic arom	
	KECI = Korea Existing Chemica	
	LC50 = Lethal Concentration fifthere	
	LD50 = Lethal Dose fifty per cen	
	LL/EL/IL = Lethal Loading/Effect	
	LL50 = Lethal Loading fifty	
	MARPOL = International Conver	ntion for the Prevention of
	Pollution From Ships	
	NOEC/NOEL = No Observed Ef	fact Concentration / No
	NUEU/NUEL = NO UDSERVED ET	rect Concentration / No

Shell Gadus S2 V100 3

Version 3.4	Revision Date 13.10.2017	Print Date 14.10.2017		
	Observed Effect Level OE_HPV = Occupational Exposure - High Production Volume PBT = Persistent, Bioaccumulative and Toxic PICCS = Philippine Inventory of Chemicals and Chemical Substances PNEC = Predicted No Effect Concentration REACH = Registration Evaluation And Authorisation Of Chemicals RID = Regulations Relating to International Carriage of Dangerous Goods by Rail SKIN_DES = Skin Designation STEL = Short term exposure limit TRA = Targeted Risk Assessment TSCA = US Toxic Substances Control Act TWA = Time-Weighted Average vPvB = very Persistent and very Bioaccumulative			
Further information				
Training advice	: Provide adequate information, in operators.	nstruction and training for		
Other information	: A vertical bar () in the left marg from the previous version.	in indicates an amendment		
Sources of key data used to compile the Safety Data Sheet	: The quoted data are from, but n sources of information (e.g. toxi Health Services, material suppli IUCLID date base, EC 1272 reg	icological data from Shell iers' data, CONCAWE, EU		

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.